

# Package ‘BaM’

July 21, 2025

**Title** Functions and Datasets for “Bayesian Methods: A Social and Behavioral Sciences Approach”

**Version** 1.0.3

**Author** Jonathan Homola, Danielle Korman, Jacob Metz, Miguel Pereira, Mauricio Vela, and Jeff Gill <jgill15402@mac.com>

**Maintainer** Jeff Gill <jgill15402@mac.com>

**Description** Functions and datasets for Jeff Gill: “Bayesian Methods: A Social and Behavioral Sciences Approach”. First, Second, and Third Edition. Published by Chapman and Hall/CRC (2002, 2007, 2014) <[doi:10.1201/b17888](https://doi.org/10.1201/b17888)>.

**Depends** R (>= 3.0.1)

**Imports** MASS, mice

**Suggests** coda, nnet

**License** GPL (>= 2)

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 7.1.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-10-14 11:25:17 UTC

## Contents

actuarial . . . . .	3
adam.jags . . . . .	3
afghan.deaths . . . . .	4
africa . . . . .	4
asap.data.list . . . . .	5
baldus . . . . .	6
bcp . . . . .	8
biv.norm.post . . . . .	8
cabinet.duration . . . . .	10

child	10
china.wars	11
coal.mining.disasters	12
contracep	12
DA_cwp	13
dmultinorm	14
dp	14
durations.hpd	15
elicspend	16
ethnic.immigration	16
executions	17
experts	17
expo.gibbs	18
expo.metrop	18
fdr	19
hanjack	19
hit.run	20
iq	21
italy.parties	22
lunatics	22
marriage.rates	22
metropolis	23
militarydf	23
nc.sub.dat	24
norm.known.var	25
normal.posterior.summary	25
norr	26
opic	26
pbc.vote	27
plot_walk_G	27
plot_walk_MH	28
recidivism	28
retail.sales	29
rmultinorm	30
romney	30
sir	31
socatt	33
strikes	34
terrorism	35
texas	35
t_ci_table	36
wars	37

---

actuarial

*actuarial*

---

**Description**

actuarial claims data for three groups of insurance policyholders p. 449

**Usage**

data(actuarial)

**Format**

dataset with 5 observations of 7 variables

**Details**

The variables included in the dataset are:

- year
- payroll for groups 1, 2, and 3
- claims for groups 1, 2, and 3

**Source**

Scollnik, D. P. M. (2001). Actuarial Modeling with MCMC and BUGS. North American Actuarial Journal 5, 95-124.

---

adam.jags

*adam.jags*

---

**Description**

data from Differences in the Validity of Self-Reported Drug Use Across Five Factors in Indianapolis, Fort Lauderdale, Phoenix, and Dallas, 1994 (ICPSR Study Number 2706, Rosay and Herz (2000), from the Arrestee Drug Abuse Monitoring (ADAM) Program/Drug Use Forecasting, ICPSR Study Number 2826. The original purpose of the study was to understand the accuracy of self-reported drug use, which is a difficult problem for obvious reasons.

The variables included in the dataset are:

- AGEGRP 1 for 1,700 cases 18 through 30 years old, 2 for 1,265 cases 31 years old or over
- CASES
- CATS
- COCSELF indicating self-reported cocaine usage prior to arrest (0 for 2,220 negative responses, 1 for 745 positive responses)

- COCTEST
- COVARS
- GROUP
- ID
- MJSELF
- MJTEST a dichotomous variable indicating a positive urine test for marijuana
- OFFENSE
- RACE 1 for 1,554 black cases, 2 for 1,411 white cases
- SEX 1 for 2,213 male cases, 2 for 752 female cases
- SITE coded according to: Indianapolis = 1 (759 cases), Ft. Lauderdale = 2 (974 cases), Phoenix = 3 (646 cases), and Dallas = 4 (586 cases)

### Usage

```
data(adam.jags)
```

---

afghan.deaths	<i>afghan.deaths</i>
---------------	----------------------

---

### Description

NATO Fatalities in Afghanistan, 10/01 to 1/07. see page 350

### Usage

```
data(afghan.deaths)
```

### Format

52 monthly periods, listed by rows

---

africa	<i>africa</i>
--------	---------------

---

### Description

African Coups Data, pp.562-564

### Usage

```
data(africa)
```

**Format**

data frame with 33 observations of different African countries' military coups with 7 explanatory variables

**Details**

The variables included in the dataset are:

- MILTCOUP Military Coups
- MILITARY Military Oligarchy
- POLLIB Political Liberalization: 0 for no observable civil rights for political expression, 1 for limited, and 2 for extensive
- PARTY93 number of legally registered political parties
- PCTVOTE Percent Legislative Voting
- PCTTURN Percent registered voting
- SIZE in one thousand square kilometer units
- POP Population in millions
- NUMREGIM Regime
- NUMELEC Election

**Source**

Bratton, M. and Van De Walle, N. (1994). Neopatrimonial Regimes and Political Transitions in Africa. *World Politics* 46, 453-489.

---

asap.data.list

*asap.data.list*

---

**Description**

The American State Administrator's Project (ASAP) survey asks administrators about the influence of a variety of external political actors including "clientele groups" in their agencies., see page 395.

The variables included in the dataset are:

- contracting scale from 0 : 6 where higher indicates more private contracting within the respondent's agency.
- gov.influence respondents' assessment of the governor's influence on contracting in their agency.
- leg.influence respondents' assessment of the legislatures' influence on contracting in their agency, ranging from 0 : 21.
- elect.board dichotomous variable coded 1 if appointed by a board, a commission or elected, and 0 otherwise.
- years.tenure number of years that the respondent has worked at their current agency.

- `education` ordinal variable for level of education possessed by the respondent.
- `partisan.ID` a 5-point ordinal variable (1-5) for the respondent's partisanship (strong Democrat to strong Republican).
- `category` categories of agency type.
- `med.time` whether the respondent spent more or less than the sample median with representatives of interest groups.
- `medt.contr` interaction variable between `med.time` and `contracting`.
- `gov.ideology` state government ideology from Berry et al. (1998) from 0 to 100.
- `lobbyists` total state lobbying registrants in 2000-01 from Gray and Lowery (1996, 2001).
- `nonprofits` provides the total number of nonprofit groups in the respondents' state in the year 2008, divided by 10,000.

### Usage

```
data(asap.data.list)
```

---

baldus	<i>Baldus Dataset</i>
--------	-----------------------

---

### Description

Data from Baldus Study on death sentences in Georgia (Exercise 14.2, p. 521). To use the data in JAGS or WinBugs, see `baldus.jags` and `balfus.winbugs`, respectively.

### Usage

```
data(baldus)
```

### Details

The variables included in the dataset are:

- `race` Defendant's race (1 = Black)
- `educatn` Educational level
- `employm` Employment status (1 = Employed)
- `SES` Socioeconomic status (1 = Low Wage)
- `married` Marital status (1 = Married)
- `num.chld` Number of children
- `military` Military experience (1 = Serving, 0 = No military service, -1 = Dishonorable Discharge)
- `pr.arrst`
- `plea` Plea to Murder Indictment
- `sentence` Sentenced

- defense Status of Principle Defense Council (1 = Retained, 2 = Appointed)
- dp.sght Prosecutor Waive/Fail to Seek DP (1 = Failed/Unknown, 2 = Sought DP)
- jdge.dec Judge Took Sentence from Jury?
- pen.phse Was there a penalty trial?
- did.appl Did defendant appeal cov. or sentence?
- out.appl Outcome of appeal
- vict.sex Victim sex
- pr.incr
- vict.age Victim's age
- vict.rel Relation of victim with defendant
- vict.st1 Victim status (0 = Non-police+judicial, 1 = Police+judicial)
- vict.st2
- specialA Special Circumstances ()
- methodA Method of killing
- num.kill Number of persons killed by defendant
- num.prps Number of persons killed by coperpetrator
- def.age Defendant's age
- aggravat Aggravating circumstances
- bloody Bloody crime
- fam.lov
- insane Defendant invoked insanity defense
- mitcir
- num.depr
- rape Rape involved

**Source**

Baldus, D. C., Pulaski, C., & Woodworth, G. (1983). Comparative review of death sentences: An empirical study of the Georgia experience. *The Journal of Criminal Law and Criminology* (1973-), 74(3), 661-753.

**See Also**

baldus.jags baldus.winbugs

bcp

*bcp*

---

**Description**

Implementation of bcp function, see pages 362-363 (2nd Edition).

**Usage**

```
bcp(theta.matrix, y, a, b, g, d)
```

**Arguments**

theta.matrix	theta.matrix
y	Counts of Coal Mining Disasters
a	Alpha Value in the lambda Prior
b	Beta Value in the lambda Prior
g	Gamma Value in the phi Prior
d	Delta Value in the phi Prior

**Author(s)**

Jeff Gill

**Examples**

```
## Not run:  
bcp(theta.matrix,y,a,b,g,d)  
  
## End(Not run)
```

---

biv.norm.post*biv.norm.post*

---

**Description**

A function to calculate posterior quantities of the bivariate normal. See page 94.

**Usage**

```
biv.norm.post(data.mat,alpha,beta,m,n0=5)
```



**Arguments**

data.mat	A matrix with two columns of normally distributed data
alpha	Wishart first (scalar) parameter
beta	Wishart second (matrix) parameter
m	prior mean for mu
n0	prior confidence parameter

**Value**

## Returns

mu2	posterior mean, dimension 1
sig1	posterior mean, dimension 2
sig2	posterior variance, dimension 1
rho	posterior variance, dimension 2

**Author(s)**

Jeff Gill

**Examples**

```

rwishart <- function(df, p = nrow(SqrtSigma), SqrtSigma = diag(p)) {
  if((Ident <- missing(SqrtSigma)) && missing(p)) stop("either p or SqrtSigma must be specified")
  Z <- matrix(0, p, p)
  diag(Z) <- sqrt(rchisq(p, df:(df-p+1)))
  if(p > 1) {
    pseq <- 1:(p-1)
    Z[rep(p*pseq, pseq) + unlist(lapply(pseq, seq))] <- rnorm(p*(p-1)/2)
  }
  if(Ident) crossprod(Z)
  else crossprod(Z %*% SqrtSigma)
}

data.n10 <- rmultinorm(10, c(1,3), matrix(c(1.0,0.7,0.7,3.0),2,2))
rep.mat <- NULL; reps <- 1000
for (i in 1:reps){
  rep.mat <- rbind(rep.mat, biv.norm.post(data.n10,3, matrix(c(10,5,5,10),2,2),c(2,2)))
}
round(normal.posterior.summary(rep.mat),3)

```

---

cabinet.duration	<i>cabinet.duration</i>
------------------	-------------------------

---

**Description**

Cabinet duration (constitutional inter-election period) for eleven Western European countries from 1945 to 1980, page 65

**Usage**

cabinet.duration

**Format**

cabinet duration of 11 countries

**Details**

The variables included in the dataset are:

- N number of cabinets
- dur average length of duration

**Note**

Row names indicate country.

**References**

Browne, E. C., Frenreis, J. P., and Gleiber, D. W. (1986). The Process of Cabinet Dissolution: An Exponential Model of Duration and Stability in Western Democracies. *American Journal of Political Science* 30, 628-650.

---

child	<i>child</i>
-------	--------------

---

**Description**

Child Support Collection Policies from 50 states from 1982-1991. See page 166

**Usage**

child

**Format**

observations of 8 variables for 50 states

**Details**

The variables included in the dataset are:

- SCCOLL Change in Child Support collections
- ACES Chapters per Population
- INSTABIL Policy Instability
- AAMBIG Policy Ambiguity
- CSTAFF Change in Agency Staffing
- ARD State Divorce Rate
- ASLACK Organizational Slack
- AEXPEND State Level Expenditures

**Source**

Meier, K.J. and Keisler, L.R. (1996). Public Administration as a Science of the Artificial: A Method for Prescription, *Public Administration Review* 56, 459-466.

---

china.wars

*china.wars*

---

**Description**

Modeling code for the example of ancient Chinese wars. See page 163-165

**Usage**

```
china.wars()
```

**Author(s)**

Jeff Gill

**Source**

Claudio Cioffi-Revilla and David Lai, 2001,  
"Chinese Warfare and Politics in the Ancient East Asian International System",  
Download from <doi:10.1080/03050620108434971>  
Henry A. Murray Research Archive  
Center for International Relations, Department of Political Science, University of Colorado, Boulder, USA

---

coal.mining.disasters *coal.mining.disasters*

---

**Description**

A vector of British Coal Mining Disasters, see page 549-550

**Usage**

coal.mining.disasters

**Format**

vector of length 111

**Source**

Lynn, R. and Vanhanen, T. (2001). National IQ and Economic Development. *Mankind Quarterly* LXI, 415-437.

---

contracep *contracep*

---

**Description**

Contraception Data by country. See page 446

**Usage**

data(contracep)

**Format**

4 variables for 15 countries

**Details**

The variables included in the dataset are:

- Country Developing countries by size
- URC Rural Childhood
- WED Years of Education for the Woman
- FPE Exposure to Family Planning Efforts
- WED.FPE Interaction term specified by Wong and Mason

**Source**

Wong, G. Y. and Mason, W. M. (1985). The Hierarchical Logistic Regression Model for Multilevel Analysis. *Journal of the American Statistical Association* 80, 513-524.

---

*DA\_cwp**DA\_cwp*

---

**Description**

Data on ancient Chinese wars

**Details**

The variables included in the dataset are:

- X1
- CHLEG010
- LEGHUANG
- X.2697
- X.2697.1
- X2
- X1.1
- X1.2
- X0
- X0.1
- X2.1
- X3
- X2.2
- X3.1
- X2.3

*dmultinorm**dmultinorm*

---

**Description**

`dmultinorm` function, see page 376.

**Usage**

```
dmultinorm(xval,yval,mu.vector,sigma.matrix)
```

**Arguments**

<code>xval</code>	Vector of X Random Variables
<code>yval</code>	Vector of Y Random Variables
<code>mu.vector</code>	Mean Vector
<code>sigma.matrix</code>	Matrix of Standard Deviations

**Author(s)**

Jeff Gill

---

*dp**dp*

---

**Description**

Death Penalty Data, See Page 142.

**Usage**

```
data(dp)
```

**Format**

7 variables for 17 states

**Details**

The variables included in the dataset are:

- X State
- EXECUTIONS Number of capital punishments at state level in 1997
- INCOME Median per capita income in dollars
- PERPOVERTY Percent classified as living in poverty
- PERBLACK Percent of black citizens in population
- VC100k96 Rate of violent crime per 100,000 residents for 1996
- SOUTH Is the state in the South?
- PROPDEGREE Proportion of population with college degree

**Source**

Norrander, B. (2000). The Multi-Layered Impact of Public Opinion on Capital Punishment Implementation in the American States. *Political Research Quarterly* 53, 771-793.

---

durations.hpd

*durations.hpd*

---

**Description**

Simple HPD calculator from Chapter 2 (page 51, 2nd Edition).

**Usage**

```
durations.hpd(support, fn.eval, start, stop, target=0.90, tol=0.01)
```

**Arguments**

support	x-axis values
fn.eval	function values at x-axis points
start	starting point in the vectors
stop	stopping point in the vectors
target	Desired X Level
tol	Tolerance for round-off

**Author(s)**

Jeff Gill

**Examples**

```
## Not run:
get("cabinet.duration")
ruler <- seq(0.45,0.75,length=10000)
g.vals <- round(dgamma(ruler,shape=sum(cabinet.duration$N),
                      rate=sum(cabinet.duration$N*cabinet.duration$dur)),2)
start.point <- 1000; stop.point <- length(g.vals)
durations.hpd(ruler,g.vals,start.point,stop.point)

## End(Not run)
```

---

elicspend	<i>elicspend</i>
-----------	------------------

---

**Description**

Eliciting expected campaign spending data. Eight campaign experts are queried for quantiles at levels  $m = [0.1, 0.5, 0.9]$ , and they provide the following values reflecting the national range of expected total intake by Senate candidates (in thousands). See page 120

**Usage**

```
data(elicspend)
```

---

ethnic.immigration	<i>ethnic.immigration</i>
--------------------	---------------------------

---

**Description**

1990-1993 W.Europe Ethnic/Minority Populations. see page 280.

**Usage**

```
data(ethnic.immigration)
```

**Format**

total number of ethnic immigrants living in Western Europe from 22 countries

**Details**

The variables included in the dataset are:

- Country.of.Origin Country of origin of immigrants
- Estimated.Total.K. Estimated total ethnic minority population in Western European Countries
- Percent.of.Total Percent of Total



**Source**

Peach, C. (1997). Postwar Migration to Europe: Reflux, Influx, Refuge. *Social Science Quarterly* 78, 269-283.

executions

*executions*

**Description**

Execution data.

The variables included in the dataset are:

- State State
- EXECUTIONS Number of capital punishments at state level in 1997
- Median.Income Median per capita income in dollars
- Percent.Poverty Percent classified as living in poverty
- Percent.Black Percent of black citizens in population
- Violent.Crime Rate of violent crime per 100,000 residents for 1996

**Usage**

data(executions)

**Format**

explanatory variables for 17 states

experts

*Campaign fundraisign elicitations*

**Description**

Fabricated data on campaign fundraising elicitations. See page 120

**Usage**

experts(q1, q2, q3)

**Arguments**

- q1                    the 0.1 quantile
- q2                    the 0.5 quantile
- q3                    the 0.9 quantile

expo.gibbs

*expo.gibbs*

---

**Description**

Simple Gibbs sampler demonstration on conditional exponentials from Chapter 1 (pages 25-27).

**Usage**

```
expo.gibbs(B,k,m)
```

**Arguments**

B	an upper bound
k	length of the subchains
m	number of iterations

**Author(s)**

Jeff Gill

---

expo.metrop

*expo.metrop*

---

**Description**

Simple Metropolis algorithm demonstration using a bivariate exponential target from Chapter 1 (pages 27-30).

**Usage**

```
expo.metrop(m,x,y,L1,L2,L,B)
```

**Arguments**

m	number of iterations
x	starting point for the x vector
y	starting point for the y vector
L1	event intensity for the x dimension
L2	event intensity for the y dimension
L	shared event intensity
B	upper bound

**Author(s)**

Jeff Gill

**Examples**

```
expo.metrop(m=5000, x=0.5, y=0.5, L1=0.5, L2=0.1, L=0.01, B=8)
```

---

*fdr**fdr*

---

**Description**

FDR election data. See page 576

The variables included in the dataset are:

- State State name
- FDR Whether or not FDR won the state in 1932 election, 1 = won, 0 = lost
- PRE .DEP Mean income per state before the Great Depression (1929), in dollars
- POST .DEP Mean income per state after the Great Depression (1932), in dollars
- FARM Total farm wage and salary disbursements in thousands of dollars per state in 1932

**Usage**

```
data(fdr)
```

---

*hanjack**hanjack*

---

**Description**

1964 presidential election data. See page 221

**Usage**

```
hanjack(N, F, L, W, K, IND, DEM, WR, WD, SD)
```

**Arguments**

N	number of cases in the group
F	Observed cell proportion voting for Johnson
L	log-ratio of this proportion, see p. 246
W	collects the inverse of the diagonal of the matrix for the group-weighting from $[N_i P_i (1 - P_i)]$
K	constant
IND	indifference to the election
DEM	stated preference for Democratic party issues
WR	Weak Republican
WD	Weak Democrat
SD	Strong Democrat

**References**

Hanushek, E. A. and Jackson, J. E. (1977). Statistical Methods for Social Scientists San Diego, Academic Press

---

*hit.run*

*hit.run*

---

**Description**

Implementation of *hit.run* algorithm, p. 361.

**Usage**

```
hit.run(theta.mat, reps, I.mat)
```

**Arguments**

<i>theta.mat</i>	<i>theta.mat</i>
<i>reps</i>	<i>reps</i>
<i>I.mat</i>	<i>I.mat</i>

**Author(s)**

Jeff Gill

**Examples**

```
## Not run:
#code to implement graph on p. 362, see page 376.

num.sims <- 10000
Sig.mat <- matrix(c(1.0,0.95,0.95,1.0),2,2)
walks<-rbind(c(-3,-3),matrix(NA,nrow=(num.sims-1),ncol=2))
walks <- hit.run(walks,num.sims,Sig.mat)
z.grid <- outer(seq(-3,3,length=100),seq(-3,3,length=100),
               FUN=dmultinorm,c(0,0),Sig.mat)
contour(seq(-3,3,length=100),seq(-3,3,length=100),z.grid,
        levels=c(0.05,0.1,0.2))
points(walks[5001:num.sims,],pch=".")
```

iq

*iq data frame***Description**

IQ data for 80 countries. See pages 85-87

**Usage**

```
data(iq)
```

**Source**

Lynn, R. and Vanhanen, T. (2001). National IQ and Economic Development. *Mankind Quarterly* LXI, 415-437.

**Examples**

```
## Not run:
{
data(iq)
n <- length(iq[1,])
t.iq <- (iq[1,]-mean(as.numeric(iq)))/(sd(iq[1,])/sqrt(n))
r.t <- (rt(100000, n-1)*(sd(iq)/sqrt(n))) + mean(as.numeric(iq))
quantile(r.t,c(0.01,0.10,0.25,0.5,0.75,0.90,0.99))
r.sigma.sq <- 1/rgamma(100000,shape=(n-2)/2, rate=var(as.numeric(iq))*(n-1)/2)
quantile(sqrt(r.sigma.sq), c(0.01,0.10,0.25,0.5,0.75,0.90,0.99))
}
## End(Not run)
```

---

italy.parties	<i>italy.parties</i>
---------------	----------------------

---

**Description**

Italian Parties Data. Vote share of Italian parties from 1948-1983. See page 370-371.

**Usage**

```
data(italy.parties)
```

---

lunatics	<i>lunatics</i>
----------	-----------------

---

**Description**

An 1854 study on mental health in the fourteen counties of Massachusetts yields data on 14 cases. This study was performed by Edward Jarvis (then president of the American Statistical Association)

The variables included in the dataset are:

- NBR the number of "lunatics" per county.
- DIST distance to the nearest mental healthcare center
- POP population in the county by thousands
- PDEN population per square county mile
- PHOME the percent of "lunatics" cared for in the home

**Usage**

```
data(lunatics)
```

---

marriage.rates	<i>Marriage Rates in Italy</i>
----------------	--------------------------------

---

**Description**

Italian Marriage Rates. See page 430

**Usage**

```
data(marriage.rates)
```

**Format**

a vector containing 16 numbers

**Source**

Columbo, B. (1952). Preliminary Analysis of Recent Demographic Trends in Italy. Population Index 18, 265-279.

---

metropolis

*metropolis*

---

**Description**

Implementation of metropolis function, p. 359.

**Usage**

```
metropolis(theta.matrix, reps, I.mat)
```

**Arguments**

theta.matrix	theta.matrix
reps	reps
I.mat	I.mat

**Author(s)**

Jeff Gill

---

militarydf

*militarydf*

---

**Description**

A dataset of two variables. The proportional changes in military personnel for the named countries. See page 483-484

The variables included in the dataset are:

- Year The year selected to evaluate
- Yugoslavia The proportion change in the size of Yugoslavia's military
- Albania The proportion change in the size of Albania's military
- Bulgaria The proportion change in the size of Bulgaria's military
- Czechoslovakia The proportion change in the size of Czechoslovakia's military

- German.Dem.Republic The proportion change in the size of the German Democratic Republic's military
- Hungary The proportion change in the size of Hungary's military
- Poland The proportion change in the size of Poland's military
- Rumania The proportion change in the size of Romania's military
- USSR The proportion change in the size of the Soviet Union's military

### Usage

```
data(militarydf)
```

### Format

a data frame with 35 observations of years from 1949 to 1983 with 10 explanatory variables

### Source

Faber, J. (1989). Annual Data on Nine Economic and Military Characteristics of 78 Nations (SIRE NATDAT), 1948-1983. Ann Arbor: Inter-University Consortium for Political and Social Research and Amsterdam, and Amsterdam, the Netherlands: Europa Institute, Steinmetz Archive.

---

nc.sub.dat

*nc.sub.dat*

---

### Description

North Carolina county level health data from the 2000 U.S. census and North Carolina public records, see page 78.

The variables included in the dataset are:

- Substantiated.Abuse within family documented abuse for the county
- Percent.Poverty percent within the county living in poverty, U.S. definition
- Total.Population county population/1000

### Usage

```
nc.sub.dat
```

### Format

data frame with 100 observations of different counties in North Carolina with 3 explanatory variables

### Source

data from 2000 US census and North Carolina Division of Public Health, Women's and Children's Health Section in Conjunction with State Center for Health Statistics



---

norm.known.var	<i>norm.known.var</i>
----------------	-----------------------

---

**Description**

A function to calculate posterior quantities for a normal-normal model with known variance (pages 70-72). It produces the posterior mean, variance, and 95% credible interval for user-specified prior.

**Usage**

```
norm.known.var(data.vec, pop.var, prior.mean, prior.var)
```

**Arguments**

data.vec	a vector of assumed normally distributed data
pop.var	known population variance
prior.mean	mean of specified prior distribution for mu
prior.var	variance of specified prior distribution for mu

**Author(s)**

Jeff Gill

---

normal.posterior.summary	<i>normal posterior summary</i>
--------------------------	---------------------------------

---

**Description**

A function to calculate posterior quantities of bivariate normals. See pages 74-80.

**Usage**

```
normal.posterior.summary(reps)
```

**Arguments**

reps	a matrix where the columns are defined as in the output of biv.norm.post:
------	---

**Author(s)**

Jeff Gill

**See Also**

[biv.norm.post](#)

---

 norr

 norr
 

---

### Description

An 1854 study on mental health in the fourteen counties of Massachusetts yields data on 14 cases. This study was performed by Edward Jarvis (then president of the American Statistical Association)

The variables included in the dataset are:

- Current.policy Current sentencing policy
- Past.execution.rate Past execution rate
- Politicla.Culture Political culture
- Current.opinion Current opinion
- Citizen.ideology Citizen ideology
- Murder.Rate Murder rate
- Catholic Catholic
- Black Black
- Urban Urban
- Past.laws Past laws
- Past.opinion Past opinion

### Usage

```
data(norr)
```

---

opic

 opic
 

---

### Description

private capital investment data. See Page 390.

The variables included in the dataset are:

- Fund Name of the private company
- Age Years the company has been in existence
- Status Whether the company is investing or divesting
- Size Maximum fund size in millions

### Usage

```
data(opic)
```

---

pbc.vote

*pbc.vote*

---

### Description

Precinct level data for Palm Beach County, Florida from the 2000 U.S. Presidential Election, see page 149

The variables included in the dataset are:

- `badballots` Total number of spoiled ballots
- `technology` Voting Technology used, 0 for a datapunch machine or a butterfly ballot, 1 for votomatic
- `new` Number of "new" voters, as in those who have not voted in the precinct for previous 6 years
- `size` Total number of precinct voters
- `Republican` The number of voters registered as Republican
- `white` The number of white nonminority voters in a given precinct

### Usage

```
data(pbc.vote)
```

### Format

data frame with 516 observations of each precinct in Palm Beach County with 11 explanatory variables

### Source

Palm Beach Post collected data from state and federal sources about precinct level data in Palm Beach County for the 2000 US presidential election

---

plot\_walk\_G

*plot\_walk\_G*

---

### Description

`plot_walk_G` code used to produce figure 10.2

### Usage

```
plot_walk_G(walk.mat, sim.rm, X=1, Y=2)
```

**Arguments**

walk.mat	walk.mat
sim.rm	sim.rm
X	X
Y	Y

**Author(s)**

Jeff Gill

---

plot_walk_MH	<i>plot_walk_MH</i>
--------------	---------------------

---

**Description**

plot\_walk\_MH code used to produce figure 10.4

**Usage**

plot\_walk\_MH(walk.mat)

**Arguments**

walk.mat	walk.mat
----------	----------

**Author(s)**

Jeff Gill

---

recidivism	<i>recidivism</i>
------------	-------------------

---

**Description**

Recidivism Rates. See page 188

The variables included in the dataset are:

- Crime.Type The type of crime committed
- Released The number of individuals released from a facility
- Returned The number of individuals returned to a facility
- Percentage (The number of individuals returned to a facility)/(The number of individuals released from a facility)

**Usage**

```
data(recidivism)
```

**Format**

data frame with 27 observations of different crime types with 5 explanatory variables

**Source**

state-level recidivism data as collected by the Oklahoma Department of Corrections from January 1, 1985 to June 30, 1999

---

retail.sales	<i>retail.sales</i>
--------------	---------------------

---

**Description**

Retail sales from 1979 through 1989 based on data provided by the U.S. Department of Commerce through the Survey of Current Business, see page 439

The variables included in the dataset are:

- TIME the economic quarter specified, starting from the first quarter of 1979 where j=1 to the fourth quarter of 1989 where j=44
- DSB national income wage and salary disbursements (in billions of dollars)
- EMP employees on non-agricultural payrolls (in thousands)
- BDG building material dealer sales (in millions of dollars)
- CAR retail automotive dealer sales (in millions of dollars)
- FRN home furnishings dealer sales (in millions of dollars)
- GMR general merchandise dealer sales (in millions of dollars)

**Usage**

```
data(retail.sales)
```

**Format**

data frame with 44 observations of statistics for different economic quarters with 7 explanatory variables

**Source**

U.S. Department of Commerce data from first quarter of 1979 to fourth quarter of 1989

*rmultinorm**rmultinorm*

---

**Description**

a function to generate random multivariate Gaussians.

**Usage**

```
rmultinorm(n, mu, vmat, tol = 1e-07)
```

**Arguments**

n	nu
mu	vector of mean
vmat	variance-covariance matrix
tol	tolerance

**Author(s)**

Jeff Gill

**See Also**

[biv.norm.post](#)

---

*romney**romney*

---

**Description**

Analysis of cultural consensus data using binomial likelihood and beta prior.

**Usage**

```
romney()
```

**Format**

See for yourself. Modify as desired.

**Author(s)**

Jeff Gill

**Source**

Romney, A. K. (1999). Culture Consensus as a Statistical Model.  
*Current Anthropology* 40 (Supplement), S103-S115.

---

 sir
 

---



---

 sir
 

---

**Description**

Implementation of Rubin's SIR, see pages 338-341 (2nd Edition)

**Usage**

```
sir(data.mat, theta.vector, theta.mat, M, m, tol=1e-06, ll.func, df=0)
```

**Arguments**

data.mat	A matrix with two columns of normally distributed data
theta.vector	The initial coefficient estimates
theta.mat	The initial vc matrix
M	The number of draws
m	The desired number of accepted values
tol	The rounding/truncing tolerance
ll.func	loglike function for empirical posterior
df	The df for using the t distribution as the approx distribution

**Author(s)**

Jeff Gill

**Examples**

```
## Not run:
sir <- function(data.mat, theta.vector, theta.mat, M, m, tol=1e-06, ll.func, df=0) {
  importance.ratio <- rep(NA, M)
  rand.draw <- rmultinorm(M, theta.vector, theta.mat, tol = 1e-04)
  if (df > 0)
    rand.draw <- rand.draw/(sqrt(rchisq(M, df)/df))
  empirical.draw.vector <- apply(rand.draw, 1, ll.func, data.mat)
  if (sum(is.na(empirical.draw.vector)) == 0) {
    print("SIR: finished generating from posterior density function")
    print(summary(empirical.draw.vector))
  }
  else {
    print(paste("SIR: found", sum(is.na(empirical.draw.vector)),
               "NA(s) in generating from posterior density function, quitting"))
  }
}
```

```

    return()
  }
  if (df == 0) {
    normal.draw.vector <- apply(rand.draw,1,normal.posterior.ll,data.mat)
  }
  else {
    theta.mat <- ((df-2)/(df))*theta.mat
    normal.draw.vector <- apply(rand.draw,1,t.posterior.ll,data.mat,df)
  }
  if (sum(is.na(normal.draw.vector)) == 0) {
    print("SIR: finished generating from approximation distribution")
    print(summary(normal.draw.vector))
  }
  else {
    print(paste("SIR: found",sum(is.na(normal.draw.vector)),
               "NA(s) in generating from approximation distribution, quitting"))
    return()
  }
  importance.ratio <- exp(empirical.draw.vector - normal.draw.vector)
  importance.ratio[is.finite=F] <- 0
  importance.ratio <- importance.ratio/max(importance.ratio)
  if (sum(is.na(importance.ratio)) == 0) {
    print("SIR: finished calculating importance weights")
    print(summary(importance.ratio))
  }
  else {
    print(paste("SIR: found",sum(is.na(importance.ratio)),
               "NA(s) in calculating importance weights, quitting"))
    return()
  }
  accepted.mat <- rand.draw[1:2,]
  while(nrow(accepted.mat) < m+2) {
    rand.unif <- runif(length(importance.ratio))
    accepted.loc <- seq(along=importance.ratio)[(rand.unif-tol) <= importance.ratio]
    rejected.loc <- seq(along=importance.ratio)[(rand.unif-tol) > importance.ratio]
    accepted.mat <- rbind(accepted.mat,rand.draw[accepted.loc,])
    rand.draw <- rand.draw[rejected.loc,]
    importance.ratio <- importance.ratio[rejected.loc]
    print(paste("SIR: cycle complete,", (nrow(accepted.mat)-2), "now accepted"))
  }
  accepted.mat[3:nrow(accepted.mat),]
}
# The following are log likelihood functions that can be plugged into the sir function above.

logit.posterior.ll <- function(theta.vector,X) {
  Y <- X[,1]
  X[,1] <- rep(1,nrow(X))
  sum( -log(1+exp(-X
                -log(1+exp(X))))))
}

normal.posterior.ll <- function(coef.vector,X) {
  dimnames(coef.vector) <- NULL

```



```

Y <- X[,1]
X[,1] <- rep(1,nrow(X))
e <- Y - X
sigma <- var(e)
return(-nrow(X)*(1/2)*log(2*pi)
       -nrow(X)*(1/2)*log(sigma)
       -(1/(2*sigma))*(t(Y-X)*(Y-X)))
}

t.posterior.ll <- function(coef.vector,X,df) {
  Y <- X[,1]
  X[,1] <- rep(1,nrow(X))
  e <- Y - X
  sigma <- var(e)*(df-2)/(df)
  d <- length(coef.vector)
  return(log(gamma((df+d)/2)) - log(gamma(df/2))
        - (d/2)*log(df)
        -(d/2)*log(pi) - 0.5*(log(sigma))
        -((df+d)/2*sigma)*log(1+(1/df)*
                               (t(Y-X*(Y-X)))))
}

probit.posterior.ll <- function (theta.vector,X,tol = 1e-05) {
  Y <- X[,1]
  X[,1] <- rep(1,nrow(X))
  Xb <- X
  h <- pnorm(Xb)
  h[h<tol] <- tol
  g <- 1-pnorm(Xb)
  g[g<tol] <- tol
  sum( log(h)*Y + log(g)*(1-Y) )
}

## End(Not run)

```

---

 socatt

 socatt
 

---

### Description

Data from the British Social Attitudes (BSA) Survey 1983-1986.

The variables included in the dataset are:

- District identifying for geographic district.
- Respondent . Code respondent identifier
- Year . Code 1 = 1983, 2 = 1984, 3 = 1985, 4 = 1986
- Num. Answers number of positive answers to seven questions
- Party 1 = Conservative, 2 = Labour, 3 = Lib/SDP/Alliance, 4 = others

- Social.Class 1 = middle, 2 = upper working, 3 = lower working
- Gender 1 = male, 2 = female.
- Age age in years 18-80
- Religion 1 = Roman Catholic, 2 = Protestant/Church of England, 3 = others, 4 = none.

### Usage

```
data(socatt)
```

---

strikes	<i>strikes</i>
---------	----------------

---

### Description

French Coal Strikes, see page 212 and 213

The variables included in the dataset are:

- Year The year the labor strikes in France occurred
- Counts The number of labor strikes that occurred in France per year

### Usage

```
data(strikes)
```

### Format

data frame with 11 observations of strikes that occurred in different years with 1 explanatory variable

### Source

Conell, C. and Cohn, S. (1995). Learning from Other People's Actions: Environmental Variation and Diffusion in French Coal Mining Strikes, 1890-1935. *American Journal of Sociology* 101, 366-403.

### Examples

```
n <- length(strikes)
r <- 1
s.y <- sum(strikes)

p.posterior.1000000 <- rbeta(1000000,n*r,s.y+0.5)
length(p.posterior.1000000[p.posterior.1000000<0.05])/1000000

par(mar=c(3,3,3,3))
ruler <- seq(0,1,length=1000)
beta.vals <- dbeta(ruler,n*r,s.y+0.5)
plot(ruler[1:200],beta.vals[1:200],yaxt="n",main="",ylab="",type="l")
```

```

mtext(side=2,line=1,"Density")
for (i in 1:length(ruler))
  if (ruler[i] < 0.05)
    segments(ruler[i],0,ruler[i],beta.vals[i])
segments(0.04,3,0.02,12.2)
text(0.02,12.8,"0.171")

```

---

terrorism

*terrorism*


---

### Description

Dataset comparing incidents of terrorism to car accidents, suicide, and murder, see page 140

The variables included in the dataset are:

- Year The given year in which the statistics occurred
- X.Terrorism The number of terrorist attacks that would occur per 100000 in the given year
- X.Car.Accidents The number of car accidents that would occur per 100000 in the given year
- X.Suicide The number of suicide that would occur per 100000 in the given year

### Usage

```
data(terrorism)
```

### Format

data frame with 14 observations of death rates for different years with 5 explanatory variables

### Source

Falkenrath, R. (2001). Analytical Models and Policy Prescription: Understanding Recent Innovation in U.S. Counterterrorism. *Studies in Conflict and Terrorism* 24, 159-181.

---

texas

*texas*


---

### Description

Poverty in Texas, see page 299

The variables included in the dataset are:

- POV a dichotomous outcome variable indicates whether 20% or more of the county's residents live in poverty
- BLK the proportion of Black residents in the county
- LAT the proportion of Latino residents in the county

- GVT a dichotomous variable indicating whether government activities contributed a weighted annual average of 25
- SVC a dichotomous variable indicating whether service activities contributed a weighted annual average of 50
- FED a dichotomous variable indicating whether federally owned lands make up 30
- XFR a dichotomous factor indicating whether income from transfer payments (federal, state, and local) contributed a weighted annual average of 25 percent or more of total personal income over the past three years
- POP the log of the county population total for 1989

**Usage**

```
data(texas)
```

---

<i>t_ci_table</i>	<i>t_ci_table</i>
-------------------	-------------------

---

**Description**

A function to calculate credible intervals and make a table. See page 169.

**Usage**

```
t_ci_table(coefs, cov.mat, level=0.95, degrees=Inf, quantiles=c(0.025, 0.500, 0.975))
```

**Arguments**

<code>coefs</code>	vector of coefficient estimates, usually posterior means
<code>cov.mat</code>	variance-covariance matrix
<code>level</code>	desired coverage level
<code>degrees</code>	degrees of freedom parameter for students-t distribution assumption
<code>quantiles</code>	vector of desired CDF points (quantiles) to return

**Value**

quantile.mat matrix of quantiles

**Author(s)**

Jeff Gill

---

wars

*wars*


---

### Description

Data for Chinese wars example, see page 163

The variables included in the dataset are:

- ONSET ratio-level variable measuring the epochal (whether historical or calendar) time of event occurrence, measured in calendar year
- TERM ratio-level variable measuring the epochal (historical) time of event conclusion, measured in calendar year
- EXTENT number of belligerents involved on all sides of the war
- ETHNIC intra-group or inter-group conflict
- DIVERSE number of ethnic groups participating as belligerents
- ALLIANCE total number of alliances among belligerents
- DYADS number of alliance pairs
- POL.LEV nominal-level variable measuring the political level of belligerent involvement regarding domestic and foreign belligerents, with a 1 for internal war, 2 for interstate war
- COMPLEX governmental level of the warring parties, where the first variable is multiplied by ten for scale purposes
- POLAR number of relatively major or great powers at the time of onset
- BALANCE the difference in military capabilities: minor-minor, minor-major, major-major
- TEMPOR type of war: protracted rivalry, integrative conquest, disintegrative/fracturing conflict, sporadic event
- SCOPE political scope of conflicts in terms of governmental units affected
- DURATION duration of conflict, measured in years

### Usage

`data(wars)`

### Format

a data frame of 104 observations of different China wars with 15 explanatory variables

### Source

Cioffi-Revilla, C. and Lai, D. (1995). War and Politics in Ancient China, 2700 B.C. to 722 B.C.: Measurement and Comparative Analysis. *Journal of Conflict Resolution* 39, 467-494.

# Index

actuarial, 3  
adam.jags, 3  
afghan.deaths, 4  
africa, 4  
AGEGRP (adam.jags), 3  
aggravat (baldus), 6  
asap.data.list, 5  
  
baldus, 6  
bcp, 8  
biv.norm.post, 8, 25, 30  
bloody (baldus), 6  
  
cabinet.duration, 10  
CASES (adam.jags), 3  
CATS (adam.jags), 3  
child, 10  
china.wars, 11  
coal.mining.disasters, 12  
COCELF (adam.jags), 3  
COCTEST (adam.jags), 3  
contracep, 12  
COVARS (adam.jags), 3  
  
DA\_cwp, 13  
def.age (baldus), 6  
defense (baldus), 6  
did.appl (baldus), 6  
dmultinorm, 14  
dp, 14  
dp.sgth (baldus), 6  
durations.hpd, 15  
  
educatn (baldus), 6  
elicspend, 16  
employ (baldus), 6  
ethnic.immigration, 16  
executions, 17  
experts, 17  
expo.gibbs, 18  
  
expo.metrop, 18  
  
fam.lov (baldus), 6  
fdr, 19  
  
GROUP (adam.jags), 3  
  
hanjack, 19  
hit.run, 20  
  
ID (adam.jags), 3  
insane (baldus), 6  
iq, 21  
italy.parties, 22  
  
jdge.dec (baldus), 6  
  
logit.posterior.ll (sir), 31  
lunatics, 22  
  
marriage.rates, 22  
married (baldus), 6  
methodA (baldus), 6  
metropolis, 23  
military (militarydf), 23  
militarydf, 23  
mitcir (baldus), 6  
MJSELF (adam.jags), 3  
MJTEST (adam.jags), 3  
  
nc.sub.dat, 24  
norm.known.var, 25  
normal.posterior.ll (sir), 31  
normal.posterior.summary, 25  
norr, 26  
num.chld (baldus), 6  
num.depr (baldus), 6  
num.kill (baldus), 6  
num.prps (baldus), 6  
  
OFFENSE (adam.jags), 3

opic, 26  
out.appl (baldus), 6  
  
pbc.vote, 27  
pen.phse (baldus), 6  
plea (baldus), 6  
plot\_walk\_G, 27  
plot\_walk\_MH, 28  
pr.arrst (baldus), 6  
pr.incr (baldus), 6  
probit.posterior.ll (sir), 31  
  
RACE (adam.jags), 3  
race (baldus), 6  
rape (baldus), 6  
recidivism, 28  
retail.sales, 29  
rmultinorm, 30  
romney, 30  
  
sentence (baldus), 6  
SES (baldus), 6  
SEX (adam.jags), 3  
sir, 31  
SITE (adam.jags), 3  
socatt, 33  
specialA (baldus), 6  
strikes, 34  
  
t\_ci\_table, 36  
t\_posterior.ll (sir), 31  
terrorism, 35  
texas, 35  
  
vict.age (baldus), 6  
vict.rel (baldus), 6  
vict.sex (baldus), 6  
vict.st1 (baldus), 6  
vict.st2 (baldus), 6  
  
wars, 37