

Package ‘CGGP’

July 21, 2025

Type Package

Title Composite Grid Gaussian Processes

Version 1.0.4

Description Run computer experiments using the adaptive composite grid algorithm with a Gaussian process model.
The algorithm works best when running an experiment that can evaluate thousands of points from a deterministic computer simulation.
This package is an implementation of a forthcoming paper by Plumlee, Erickson, Ankenman, et al. For a preprint of the paper, contact the maintainer of this package.

License GPL-3

Imports Rcpp (>= 0.12.18)

LinkingTo Rcpp, RcppArmadillo

Suggests testthat, covr, ggplot2, reshape2, plyr, MASS, rmarkdown, knitr

URL <https://github.com/CollinErickson/CGGP>

BugReports <https://github.com/CollinErickson/CGGP/issues>

Encoding UTF-8

RoxygenNote 7.2.3

VignetteBuilder knitr

NeedsCompilation yes

Author Collin Erickson [aut, cre],
Matthew Plumlee [aut]

Maintainer Collin Erickson <collinberickson@gmail.com>

Repository CRAN

Date/Publication 2024-01-23 03:22:57 UTC

Contents

CGGP	3
CGGPappend	3
CGGPcreate	4
CGGPfit	5
CGGPplotblocks	6
CGGPplotblocksselection	7
CGGPplotcorr	7
CGGPplotheat	8
CGGPplohist	9
CGGPplotsamplesneglogpost	10
CGGPplotslice	11
CGGPplottheta	12
CGGPplotvariogram	13
CGGPvalplot	13
CGGPvalstats	14
CGGP_internal_calcMSE	15
CGGP_internal_calcMSEde	16
CGGP_internal_calcpw	16
CGGP_internal_calcpwanddpw	17
CGGP_internal_CorrMatCauchy	18
CGGP_internal_CorrMatCauchySQ	19
CGGP_internal_CorrMatCauchySQT	20
CGGP_internal_CorrMatGaussian	21
CGGP_internal_CorrMatMatern32	22
CGGP_internal_CorrMatMatern52	23
CGGP_internal_CorrMatPowerExp	24
CGGP_internal_CorrMatWendland0	25
CGGP_internal_CorrMatWendland1	26
CGGP_internal_CorrMatWendland2	27
CGGP_internal_gneglogpost	28
CGGP_internal_MSEpredcalc	29
CGGP_internal_neglogpost	30
CGGP_internal_set_corr	31
plot.CGGP	31
predict.CGGP	32
print.CGGP	33
rpp_fastmatcler	34
rpp_fastmatcleranddcler	34
rpp_gkronDBS	35
rpp_kronDBS	35
valplot	36
valstats	37

 CGGP

CGGP: A package for running sparse grid computer experiments

Description

The CGGP package implements the method presented in Plumlee et al. (2019).

CGGP functions

The CGGP functions: `CGGPcreate`, `CGGPfit`, `CGGPappend`, and `CGGPpred`

 CGGPappend

Add points to CGGP

Description

Add ‘batchsize’ points to ‘SG’ using ‘theta’.

Usage

```
CGGPappend(CGGP, batchsize, selectionmethod = "MAP")
```

Arguments

CGGP Sparse grid object

batchsize Number of points to add

selectionmethod

How points will be selected: one of ‘UCB’, ‘TS’, ‘MAP’, ‘Oldest’, ‘Random’, or ‘Lowest’. ‘UCB’ uses Upper Confidence Bound estimates for the parameters. ‘TS’ uses Thompson sampling, a random sample from the posterior. ‘MAP’ uses maximum a posteriori parameter estimates. ‘Oldest’ adds the block that has been available the longest. ‘Random’ adds a random block. ‘Lowest’ adds the block with the lowest sum of index levels. ‘UCB’ and ‘TS’ are based on bandit algorithms and account for uncertainty in the parameter estimates, but are the slowest. ‘MAP’ is fast but doesn’t account for parameter uncertainty. The other three are naive methods that are not adaptive and won’t perform well.

Value

SG with new points added.

See Also

Other CGGP core functions: [CGGPcreate\(\)](#), [CGGPfit\(\)](#), [predict.CGGP\(\)](#)

Examples

```

SG <- CGGPcreate(d=3, batchsize=100)
y <- apply(SG$design, 1, function(x){x[1]+x[2]^2})
SG <- CGGPfit(SG, Y=y)
SG <- CGGPappend(CGGP=SG, batchsize=20, selectionmethod="MAP")

```

CGGPcreate	<i>Create sparse grid GP</i>
------------	------------------------------

Description

Create sparse grid GP

Usage

```

CGGPcreate(
  d,
  batchsize,
  corr = "PowerExponential",
  grid_sizes = c(1, 2, 4, 4, 8, 12, 20, 28, 32),
  Xs = NULL,
  Ys = NULL,
  HandlingSuppData = "Correct",
  supp_args = list()
)

```

Arguments

d	Input dimension
batchsize	Number added to design each batch for now only on predictions
corr	Name of correlation function to use. Must be one of "CauchySQT", "CauchySQ", "Cauchy", "Gaussian", "PowerExp", "Matern32", "Matern52".
grid_sizes	Size of grid refinements.
Xs	Supplemental X data
Ys	Supplemental Y data
HandlingSuppData	How should supplementary data be handled? * Correct: full likelihood with grid and supplemental data * Only: only use supplemental data * Ignore: ignore supplemental data
supp_args	Arguments used to fit if Xs and Ys are given

Value

CGGP

See Also

Other CGGP core functions: [CGGPappend\(\)](#), [CGGPfit\(\)](#), [predict.CGGP\(\)](#)

Examples

```
CGGPcreate(d=8,200)
```

CGGPfit

Update CGGP model given data

Description

This function will update the GP parameters for a CGGP design.

Usage

```
CGGPfit(
  CGGP,
  Y,
  Xs = NULL,
  Ys = NULL,
  theta0 = pmax(pmin(CGGP$thetaMAP, 0.8), -0.8),
  HandlingSuppData = CGGP$HandlingSuppData,
  separateoutputparameterdimensions = is.matrix(CGGP$thetaMAP),
  set_thetaMAP_to,
  corr,
  Ynew
)
```

Arguments

CGGP	Sparse grid objects
Y	Output values calculated at CGGP\$design
Xs	Supplemental X matrix
Ys	Supplemental Y values
theta0	Initial theta
HandlingSuppData	How should supplementary data be handled? * Correct: full likelihood with grid and supplemental data * Only: only use supplemental data * Ignore: ignore supplemental data
separateoutputparameterdimensions	If multiple output dimensions, should separate parameters be fit to each dimension?
set_thetaMAP_to	Value for thetaMAP to be set to
corr	Will update correlation function, if left missing it will be same as last time.
Ynew	Values of 'CGGP\$design_unevaluated'

Value

Updated CGGP object fit to data given

See Also

Other CGGP core functions: [CGGPappend\(\)](#), [CGGPcreate\(\)](#), [predict.CGGP\(\)](#)

Examples

```
cg <- CGGPcreate(d=3, batchsize=100)
y <- apply(cg$design, 1, function(x){x[1]+x[2]^2})
cg <- CGGPfit(CGGP=cg, Y=y)
```

CGGPplotblocks

CGGP block plot

Description

Plot the 2D projections of the blocks of an CGGP object.

Usage

```
CGGPplotblocks(CGGP, singleplot = TRUE)
```

Arguments

CGGP	CGGP object
singleplot	If only two dimensions, should a single plot be made?

Value

ggplot2 plot

See Also

Other CGGP plot functions: [CGGPplotcorr\(\)](#), [CGGPplotheat\(\)](#), [CGGPplohist\(\)](#), [CGGPplotsamplesneglogpost\(\)](#), [CGGPplotslice\(\)](#), [CGGPplottheta\(\)](#), [CGGPplotvariogram\(\)](#), [CGGPvalplot\(\)](#)

Examples

```
# The first and fourth dimensions are most active and will have greater depth
ss <- CGGPcreate(d=5, batchsize=50)
f <- function(x) {cos(2*pi*x[1]*3) + x[3]*exp(4*x[4])}
ss <- CGGPfit(ss, Y=apply(ss$design, 1, f))
ss <- CGGPappend(CGGP=ss, batchsize=100)
CGGPplotblocks(ss)

mat <- matrix(c(1,1,1,2,2,1,2,2,1,3), ncol=2, byrow=TRUE)
CGGPplotblocks(mat)
```

`CGGPplotblockselection`*Plot CGGP block selection over time*

Description

Shows the order in which blocks were selected for each dimension. Gives an idea of how the selections change over time.

Usage

```
CGGPplotblockselection(CGGP, indims)
```

Arguments

<code>CGGP</code>	CGGP object
<code>indims</code>	Which input dimensions should be shown?

Value

ggplot2 object

Examples

```
gs <- CGGPcreate(d=3, batchsize=100)
# All dimensions will look similar
CGGPplotblockselection(gs)

# You need to append with CGGPappend after fitting to see a difference
f <- function(x){x[1]^1.2}
y <- apply(gs$design, 1, f)
gs <- CGGPfit(gs, Y=y)
gs <- CGGPappend(gs, 100)
# Now you will see higher for X1 from 100 to 200 while others remain low.
CGGPplotblockselection(gs)
```

`CGGPplotcorr`*Plot correlation samples*

Description

Plot samples for a given correlation function and parameters. Useful for getting an idea of what the correlation parameters mean in terms of smoothness.

Usage

```
CGGPplotcorr(
  Corr = CGGP_internal_CorrMatGaussian,
  theta = NULL,
  numlines = 20,
  outdims = NULL,
  zero = TRUE
)
```

Arguments

Corr	Correlation function or CGGP object. If CGGP object, it will make plots for thetaMAP, the max a posteriori theta.
theta	Parameters for Corr
numlines	Number of sample paths to draw
outdims	Which output dimensions should be used?
zero	Should the sample paths start at y=0?

Value

Plot

See Also

Other CGGP plot functions: [CGGPplotblocks\(\)](#), [CGGPplothet\(\)](#), [CGGPplohist\(\)](#), [CGGPplotsamplesneglogpost\(\)](#), [CGGPplotslice\(\)](#), [CGGPplottheta\(\)](#), [CGGPplotvariogram\(\)](#), [CGGPvalplot\(\)](#)

Examples

```
CGGPplotcorr()
CGGPplotcorr(theta=c(-2,-1,0,1))

SG <- CGGPcreate(d=3, batchsize=100)
f <- function(x){x[1]^1.2+sin(2*pi*x[2]*3)}
y <- apply(SG$design, 1, f)
SG <- CGGPfit(SG, Y=y)
CGGPplotcorr(SG)
```

CGGPplothet

Heatmap of SG design depth

Description

The values on the diagonal are largest design depth for that dimension. The off-diagonal values are the largest design depth that both dimensions have been measured at simultaneously. A greater depth means that more points have been measured along that dimension or two-dimensional sub-space.

Usage

```
CGGPplotheat(CGGP)
```

Arguments

```
CGGP          CGGP object
```

Value

A heat map made from ggplot2

References

<https://stackoverflow.com/questions/14290364/heatmap-with-values-ggplot2>

See Also

Other CGGP plot functions: [CGGPplotblocks\(\)](#), [CGGPplotcorr\(\)](#), [CGGPplothist\(\)](#), [CGGPplotsamplesneglogpost\(\)](#), [CGGPplotslice\(\)](#), [CGGPplottheta\(\)](#), [CGGPplotvariogram\(\)](#), [CGGPvalplot\(\)](#)

Examples

```
# All dimensions should look similar
d <- 8
SG = CGGPcreate(d,201)
CGGPplotheat(SG)

# The first and fourth dimensions are most active and will have greater depth
SG <- CGGPcreate(d=5, batchsize=50)
f <- function(x) {cos(2*pi*x[1]*3) + exp(4*x[4])}
for (i in 1:1) {
  SG <- CGGPfit(SG, Y=apply(SG$design, 1, f))
  SG <- CGGPappend(CGGP=SG, batchsize=200)
}
# SG <- CGGPfit(SG, Y=apply(SG$design, 1, f))
CGGPplotheat(SG)
```

CGGPplothist

Histogram of measurements at each design depth of each input dimension

Description

A greater design depth signifies a more important dimension. Thus a larger right tail on the histogram are more important variables.

Usage

```
CGGPplothist(CGGP, ylog = TRUE)
```

Arguments

CGGP	CGGP object
ylog	Should the y axis be put on a log scale?

Value

Histogram plot made using ggplot2

See Also

Other CGGP plot functions: [CGGPplotblocks\(\)](#), [CGGPplotcorr\(\)](#), [CGGPplotheat\(\)](#), [CGGPplotsamplesneglogpost\(\)](#), [CGGPplotslice\(\)](#), [CGGPplottheta\(\)](#), [CGGPplotvariogram\(\)](#), [CGGPvalplot\(\)](#)

Examples

```
# All dimensions should look similar
d <- 8
SG = CGGPcreate(d,201)
CGGPplothist(SG)
CGGPplothist(SG, ylog=FALSE)

# The first dimension is more active and will have greater depth
f <- function(x) {sin(x[1]^0.6*5)}
SG <- CGGPcreate(d=5, batchsize=100)
SG <- CGGPfit(SG, apply(SG$design, 1, f))
SG <- CGGPappend(CGGP=SG, batchsize=1000)
CGGPplothist(SG)
```

CGGPplotsamplesneglogpost

Plot negative log posterior likelihood of samples

Description

Plot negative log posterior likelihood of samples

Usage

```
CGGPplotsamplesneglogpost(CGGP)
```

Arguments

CGGP	CGGP object
------	-------------

Value

ggplot2 object

See Also

Other CGGP plot functions: [CGGPplotblocks\(\)](#), [CGGPplotcorr\(\)](#), [CGGPplotheat\(\)](#), [CGGPplohist\(\)](#), [CGGPplotslice\(\)](#), [CGGPplottheta\(\)](#), [CGGPplotvariogram\(\)](#), [CGGPvalplot\(\)](#)

Examples

```
gs <- CGGPcreate(d=3, batchsize=100)
f <- function(x){x[1]^1.2+x[3]^.4*sin(2*pi*x[2]^2*3) + .1*exp(3*x[3])}
y <- apply(gs$design, 1, f)
gs <- CGGPfit(gs, Y=y)
CGGPplotsamplesneglogpost(gs)
```

CGGPplotslice

CGGP slice plot

Description

Show prediction plots when varying over only one dimension. Most useful when setting all values to 0.5 because it will have the most points.

Usage

```
CGGPplotslice(
  CGGP,
  proj = 0.5,
  np = 300,
  color = "pink",
  outdims,
  scales = "free_y",
  facet = "grid"
)
```

Arguments

CGGP	CGGP object
proj	Point to project onto
np	Number of points to use along each dimension
color	Color to make error region
outdims	If multiple outputs, which of them should be plotted?
scales	Parameter passed to <code>ggplot2::facet_grid()</code>
facet	If "grid", will use <code>ggplot2::facet_grid()</code> , if "wrap" will use <code>ggplot2::facet_wrap()</code> . Only applicable for a single output dimension.

Value

ggplot2 object

See Also

Other CGGP plot functions: [CGGPplotblocks\(\)](#), [CGGPplotcorr\(\)](#), [CGGPplotheat\(\)](#), [CGGPplothist\(\)](#), [CGGPplotsamplesneglogpost\(\)](#), [CGGPplottheta\(\)](#), [CGGPplotvariogram\(\)](#), [CGGPvalplot\(\)](#)

Examples

```
d <- 5
f1 <- function(x){x[1]+x[2]^2 + cos(x[3]^2*2*pi*4) - 3.3}
s1 <- CGGPcreate(d, 200)
s1 <- CGGPfit(s1, apply(s1$design, 1, f1))
#s1 <- CGGPappend(s1, 200)
#s1 <- CGGPfit(s1, apply(s1$design, 1, f1))
CGGPplotslice(s1)
CGGPplotslice(s1, 0.)
CGGPplotslice(s1, s1$design[nrow(s1$design),])
```

CGGPplottheta

Plot theta samples

Description

Plot theta samples

Usage

```
CGGPplottheta(CGGP)
```

Arguments

CGGP CGGP object

Value

ggplot2 object

See Also

Other CGGP plot functions: [CGGPplotblocks\(\)](#), [CGGPplotcorr\(\)](#), [CGGPplotheat\(\)](#), [CGGPplothist\(\)](#), [CGGPplotsamplesneglogpost\(\)](#), [CGGPplotslice\(\)](#), [CGGPplotvariogram\(\)](#), [CGGPvalplot\(\)](#)

Examples

```
gs <- CGGPcreate(d=3, batchsize=100)
f <- function(x){x[1]^1.2+x[3]^0.4*sin(2*pi*x[2]^2*3) + .1*exp(3*x[3])}
y <- apply(gs$design, 1, f)
gs <- CGGPfit(gs, Y=y)
CGGPplottheta(gs)
```

CGGPplotvariogram *Plot something similar to a semivariogram*

Description

It's not actually a variogram or semivariogram. It shows how the correlation function falls off as distance increases.

Usage

```
CGGPplotvariogram(CGGP, facet = 1, outdims = NULL)
```

Arguments

CGGP	CGGP object
facet	How should the plots be faceted? If 1, in a row, if 2, in a column, if 3, wrapped around.
outdims	Which output dimensions should be shown.

Value

ggplot2 object

See Also

Other CGGP plot functions: [CGGPplotblocks\(\)](#), [CGGPplotcorr\(\)](#), [CGGPplotheat\(\)](#), [CGGPplothist\(\)](#), [CGGPplotsamplesneglogpost\(\)](#), [CGGPplotslice\(\)](#), [CGGPplottheta\(\)](#), [CGGPvalplot\(\)](#)

Examples

```
SG <- CGGPcreate(d=3, batchsize=100)
f <- function(x){x[1]^1.2+x[3]^0.4*sin(2*pi*x[2]^2*3) + .1*exp(3*x[3])}
y <- apply(SG$design, 1, f)
SG <- CGGPfit(SG, Y=y)
CGGPplotvariogram(SG)
```

CGGPvalplot *Plot validation prediction errors for CGGP object*

Description

Plot validation prediction errors for CGGP object

Usage

```
CGGPvalplot(CGGP, Xval, Yval, d = NULL)
```

Arguments

CGGP	CGGP object that has been fitted
Xval	X validation data
Yval	Y validation data
d	If output is multivariate, which column to use. Will do all if left as NULL.

Value

None, makes a plot

See Also

Other CGGP plot functions: [CGGPplotblocks\(\)](#), [CGGPplotcorr\(\)](#), [CGGPplotheat\(\)](#), [CGGPplohist\(\)](#), [CGGPplotsamplesneglogpost\(\)](#), [CGGPplotslice\(\)](#), [CGGPplottheta\(\)](#), [CGGPplotvariogram\(\)](#)

Examples

```
SG <- CGGPcreate(d=3, batchsize=100)
f1 <- function(x){x[1]+x[2]^2}
y <- apply(SG$design, 1, f1)
SG <- CGGPfit(SG, y)
Xval <- matrix(runif(3*100), ncol=3)
Yval <- apply(Xval, 1, f1)
CGGPvalplot(CGGP=SG, Xval=Xval, Yval=Yval)
```

CGGPvalstats

Calculate stats for CGGP prediction on validation data

Description

Calculate stats for CGGP prediction on validation data

Usage

```
CGGPvalstats(CGGP, Xval, Yval, bydim = TRUE, ...)
```

Arguments

CGGP	CGGP object
Xval	X validation matrix
Yval	Y validation data
bydim	If multiple outputs, should it be done separately by dimension?
...	Passed to valstats, such as which stats to calculate.

Value

data frame

Examples

```

SG <- CGGPcreate(d=3, batchsize=100)
f1 <- function(x){x[1]+x[2]^2}
y <- apply(SG$design, 1, f1)
SG <- CGGPfit(SG, y)
Xval <- matrix(runif(3*100), ncol=3)
Yval <- apply(Xval, 1, f1)
CGGPvalstats(CGGP=SG, Xval=Xval, Yval=Yval)

# Multiple outputs
SG <- CGGPcreate(d=3, batchsize=100)
f1 <- function(x){x[1]+x[2]^2}
f2 <- function(x){x[1]^1.3+.4*sin(6*x[2])+10}
y1 <- apply(SG$design, 1, f1)#+rnorm(1,0,.01)
y2 <- apply(SG$design, 1, f2)#+rnorm(1,0,.01)
y <- cbind(y1, y2)
SG <- CGGPfit(SG, Y=y)
Xval <- matrix(runif(3*100), ncol=3)
Yval <- cbind(apply(Xval, 1, f1),
              apply(Xval, 1, f2))
CGGPvalstats(SG, Xval, Yval)
CGGPvalstats(SG, Xval, Yval, bydim=FALSE)

```

CGGP_internal_calcMSE *Calculate MSE over single dimension*

Description

Calculated using grid of integration points. Can be calculated exactly, but not much reason in 1D.

Usage

```
CGGP_internal_calcMSE(x1, theta, CorrMat)
```

Arguments

x1	Vector of points in 1D
theta	Correlation parameters
CorrMat	Function that gives correlation matrix for vectors of 1D points.

Value

MSE value

Examples

```
CGGP_internal_calcMSE(x1=c(0,.5,.9), theta=c(1,2,3),
                      CorrMat=CGGP_internal_CorrMatCauchySQT)
```

 CGGP_internal_calcMSEde

Calculate MSE over blocks

Description

Delta of adding block is product over $i=1..d$ of $IMSE(i,j-1) - IMSE(i,j)$

Usage

```
CGGP_internal_calcMSEde(valsinds, MSE_MAP)
```

Arguments

valsinds	Block levels to calculate MSEs for
MSE_MAP	Matrix of MSE values

Value

All MSE values

Examples

```
SG <- CGGPcreate(d=3, batchsize=100)
y <- apply(SG$design, 1, function(x){x[1]+x[2]^2})
SG <- CGGPfit(SG, Y=y)
MSE_MAP <- outer(1:SG$d, 1:8,
  Vectorize(function(dimlcv, lcv1) {
    CGGP_internal_calcMSE(SG$xb[1:SG$sizeest[dimlcv]],
      theta=SG$thetaMAP[(dimlcv-1)*SG$numpara+1:SG$numpara],
      CorrMat=SG$CorrMat)
  }))
CGGP_internal_calcMSEde(SG$po[1:SG$poCOUNT, ], MSE_MAP)
```

 CGGP_internal_calcpw *Calculate predictive weights for CGGP*

Description

Predictive weights are $\Sigma^{-1}y$ in standard GP. This calculation is much faster since we don't need to solve the full system of equations.

Usage

```
CGGP_internal_calcpw(CGGP, y, theta, return_ls = FALSE)
```


Arguments

CGGP	CGGP object
y	Measured values for CGGP\$design
theta	Correlation parameters
return_1S	Should 1S be returned?

Value

Vector with predictive weights

Examples

```
cggp <- CGGPcreate(d=3, batchsize=100)
y <- apply(cggp$design, 1, function(x){x[1]+x[2]^2+rnorm(1,0,.01)})
CGGP_internal_calcpw(CGGP=cggp, y=y, theta=cggp$thetaMAP)
```

CGGP_internal_calcpwanddpw

Calculate derivative of pw

Description

Calculate derivative of pw

Usage

```
CGGP_internal_calcpwanddpw(CGGP, y, theta, return_1S = FALSE)
```

Arguments

CGGP	CGGP object
y	Measured values for CGGP\$design
theta	Correlation parameters
return_1S	Should 1S and d1S be returned?

Value

derivative matrix of pw with respect to logtheta

Examples

```
cggp <- CGGPcreate(d=3, batchsize=100)
y <- apply(cggp$design, 1, function(x){x[1]+x[2]^2+rnorm(1,0,.01)})
CGGP_internal_calcpwanddpw(CGGP=cggp, y=y, theta=cggp$thetaMAP)
```

CGGP_internal_CorrMatCauchy
Cauchy correlation function

Description

Calculate correlation matrix for two sets of points in one dimension. Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatCauchy(
  x1,
  x2,
  theta,
  return_dCdtheta = FALSE,
  return_numpara = FALSE,
  returnlogs = FALSE
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQT\(\)](#), [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatCauchy(c(0,.2,.4),c(.1,.3,.5), theta=c(-1,.9,.1))
```

CGGP_internal_CorrMatCauchySQ
CauchySQ correlation function

Description

Calculate correlation matrix for two sets of points in one dimension Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatCauchySQ(
  x1,
  x2,
  theta,
  return_dCdtheta = FALSE,
  return_numpara = FALSE,
  returnlogs = FALSE
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatCauchySQ(c(0,.2,.4),c(.1,.3,.5), theta=c(-.7,-.5))
```

CGGP_internal_CorrMatCauchySQT
CauchySQT correlation function

Description

Calculate correlation matrix for two sets of points in one dimension. Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatCauchySQT(
  x1,
  x2,
  theta,
  return_dCdtheta = FALSE,
  return_numpara = FALSE,
  returnlogs = FALSE
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatCauchySQT(c(0,.2,.4),c(.1,.3,.5), theta=c(-.1,.3,-.7))
```

CGGP_internal_CorrMatGaussian
Gaussian correlation function

Description

Calculate correlation matrix for two sets of points in one dimension Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatGaussian(  
  x1,  
  x2,  
  theta,  
  return_dCdtheta = FALSE,  
  return_numpara = FALSE,  
  returnlogs = FALSE  
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none">• LS Log of parameter that controls lengthscale• FD Logit of $0.5 \times \text{parameter}$ that controls the fractal dimension• HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Details

WE HIGHLY ADVISE NOT USING THIS CORRELATION FUNCTION. Try Power Exponential, CauchySQT, Cauchy, or Matern 3/2 instead.

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQT\(\)](#), [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatGaussian(c(0,.2,.4),c(.1,.3,.5), theta=c(-.7))
```

```
CGGP_internal_CorrMatMatern32
```

Matern 3/2 correlation function

Description

Calculate correlation matrix for two sets of points in one dimension. Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatMatern32(  
  x1,  
  x2,  
  theta,  
  return_dCdtheta = FALSE,  
  return_numpara = FALSE,  
  returnlogs = FALSE  
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQT\(\)](#), [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatMatern32(c(0,.2,.4),c(.1,.3,.5), theta=c(-.7))
```

```
CGGP_internal_CorrMatMatern52
```

Matern 5/2 correlation function

Description

Calculate correlation matrix for two sets of points in one dimension. Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatMatern52(  
  x1,  
  x2,  
  theta,  
  return_dCdtheta = FALSE,  
  return_numpara = FALSE,  
  returnlogs = FALSE  
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQT\(\)](#), [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatMatern52(c(0,.2,.4),c(.1,.3,.5), theta=c(-.7))
```

```
CGGP_internal_CorrMatPowerExp
```

Power exponential correlation function

Description

Calculate correlation matrix for two sets of points in one dimension. Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatPowerExp(
  x1,
  x2,
  theta,
  return_dCdtheta = FALSE,
  return_numpara = FALSE,
  returnlogs = FALSE
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQT\(\)](#), [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatPowerExp(c(0,.2,.4),c(.1,.3,.5), theta=c(-.7,.2))
```

```
CGGP_internal_CorrMatWendland0
```

Wendland0 (Triangle) correlation function

Description

Calculate correlation matrix for two sets of points in one dimension. Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatWendland0(
  x1,
  x2,
  theta,
  return_dCdtheta = FALSE,
  return_numpara = FALSE,
  returnlogs = FALSE
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQT\(\)](#), [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatWendland0(c(0,.2,.4),c(.1,.3,.5), theta=-.7)
```

```
CGGP_internal_CorrMatWendland1
```

Wendland1 1 correlation function

Description

Calculate correlation matrix for two sets of points in one dimension. Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatWendland1(
  x1,
  x2,
  theta,
  return_dCdtheta = FALSE,
  return_numpara = FALSE,
  returnlogs = FALSE
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQT\(\)](#), [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland2\(\)](#)

Examples

```
CGGP_internal_CorrMatWendland1(c(0,.2,.4),c(.1,.3,.5), theta=-.7)
```

```
CGGP_internal_CorrMatWendland2
      Wendland2 2 correlation function
```

Description

Calculate correlation matrix for two sets of points in one dimension. Note that this is not the correlation between two vectors.

Usage

```
CGGP_internal_CorrMatWendland2(
  x1,
  x2,
  theta,
  return_dCdtheta = FALSE,
  return_numpara = FALSE,
  returnlogs = FALSE
)
```

Arguments

x1	Vector of coordinates from same dimension
x2	Vector of coordinates from same dimension
theta	Correlation parameters: <ul style="list-style-type: none"> • LS Log of parameter that controls lengthscale • FD Logit of 0.5*parameter that controls the fractal dimension • HE Log of parameter that controls the hurst effect
return_dCdtheta	Should dCdtheta be returned?
return_numpara	Should it just return the number of parameters?
returnlogs	Should log of correlation be returned?

Value

Matrix of correlation values between x1 and x2

See Also

Other correlation functions: [CGGP_internal_CorrMatCauchySQT\(\)](#), [CGGP_internal_CorrMatCauchySQ\(\)](#), [CGGP_internal_CorrMatCauchy\(\)](#), [CGGP_internal_CorrMatGaussian\(\)](#), [CGGP_internal_CorrMatMatern32\(\)](#), [CGGP_internal_CorrMatMatern52\(\)](#), [CGGP_internal_CorrMatPowerExp\(\)](#), [CGGP_internal_CorrMatWendland0\(\)](#), [CGGP_internal_CorrMatWendland1\(\)](#)

Examples

```
CGGP_internal_CorrMatWendland2(c(0,.2,.4),c(.1,.3,.5), theta=-.7)
```

```
CGGP_internal_gneglogpost
```

Gradient of negative log likelihood posterior

Description

Gradient of negative log likelihood posterior

Usage

```
CGGP_internal_gneglogpost(  
  theta,  
  CGGP,  
  y,  
  ...,  
  return_lik = FALSE,  
  ys = NULL,  
  Xs = NULL,  
  HandlingSuppData = "Correct"  
)
```

Arguments

theta	Log of correlation parameters
CGGP	CGGP object
y	CGGP\$design measured values
...	Forces you to name remaining arguments
return_lik	If yes, it returns a list with lik and glik
ys	Supplementary output data
Xs	Supplementary input data
HandlingSuppData	How should supplementary data be handled? * Correct: full likelihood with grid and supplemental data * Only: only use supplemental data * Ignore: ignore supplemental data

Value

Vector for gradient of likelihood w.r.t. x (theta)

Examples

```
cg <- CGGPcreate(d=3, batchsize=20)
Y <- apply(cg$design, 1, function(x){x[1]+x[2]^2})
cg <- CGGPfit(cg, Y)
CGGP_internal_neglogpost(cg$thetaMAP, CGGP=cg, y=cg$y)
```

CGGP_internal_MSEpredcalc

Calculate MSE prediction along a single dimension

Description

Calculate MSE prediction along a single dimension

Usage

```
CGGP_internal_MSEpredcalc(xp, x1, theta, CorrMat)
```

Arguments

xp	Points at which to calculate MSE
x1	Levels along dimension, vector???
theta	Correlation parameters
CorrMat	Function that gives correlation matrix for vectors of 1D points.

Value

MSE predictions

Examples

```
CGGP_internal_MSEpredcalc(c(.4,.52), c(0,.25,.5,.75,1), theta=c(.1,.2),
  CorrMat=CGGP_internal_CorrMatCauchySQ)
```

CGGP_internal_neglogpost
Calculate negative log posterior

Description

Calculate negative log posterior

Usage

```
CGGP_internal_neglogpost(
  theta,
  CGGP,
  y,
  ...,
  ys = NULL,
  Xs = NULL,
  HandlingSuppData = "Correct"
)
```

Arguments

theta	Correlation parameters
CGGP	CGGP object
y	Measured values of CGGP\$design
...	Forces you to name remaining arguments
ys	Supplementary output data
Xs	Supplementary input data
HandlingSuppData	How should supplementary data be handled?

- Correct: full likelihood with grid and supplemental data
- Only: only use supplemental data
- Ignore: ignore supplemental data

Value

Likelihood

Examples

```
cg <- CGGPcreate(d=3, batchsize=20)
Y <- apply(cg$design, 1, function(x){x[1]+x[2]^2})
cg <- CGGPfit(cg, Y)
CGGP_internal_neglogpost(cg$thetaMAP, CGGP=cg, y=cg$y)
```

 CGGP_internal_set_corr

Set correlation function of CGGP object

Description

Set correlation function of CGGP object

Usage

```
CGGP_internal_set_corr(CGGP, corr)
```

Arguments

CGGP	CGGP object
corr	Correlation function

Value

CGGP object

Examples

```
obj <- CGGPcreate(3, 20, corr="matern52")
CGGP_internal_set_corr(obj, "gaussian")
```

 plot.CGGP

S3 plot method for CGGP

Description

There are a few different plot functions for CGGP objects: ‘CGGPplotblocks’, ‘CGGPplotblock-selection’, ‘CGGPplotcorr’, ‘CGGPplotheat’, ‘CGGPplothis’, ‘CGGPvalplot’, ‘CGGPplotslice’, ‘CGGPplotslice’, and ‘CGGPplotvariogram’. Currently ‘CGGPplotblocks’ is the default plot object.

Usage

```
## S3 method for class 'CGGP'
plot(x, y, ...)
```

Arguments

x	CGGP object
y	Don't use
...	Passed to CGGPplotblocks

Value

Either makes plot or returns plot object

Examples

```
SG = CGGPcreate(3,100)
plot(SG)
```

predict.CGGP

S3 predict method for CGGP

Description

Passes to CGGPpred

Predict using SG with y values at xp? Shouldn't y values already be stored in SG?

Usage

```
## S3 method for class 'CGGP'
predict(object, xp, ...)

CGGPpred(CGGP, xp, theta = NULL, outdims = NULL)
```

Arguments

object	CGGP object
xp	x value to predict at
...	Other arguments passed to 'CGGPpred'
CGGP	SG object
theta	Leave as NULL unless you want to use a value other than thetaMAP. Much slower.
outdims	If multiple outputs fit without PCA and with separate parameters, you can predict just for certain dimensions to speed it up. Will leave other columns in the output, but they will be wrong.

Value

Predicted mean values

See Also

Other CGGP core functions: [CGGPappend\(\)](#), [CGGPcreate\(\)](#), [CGGPfit\(\)](#)

Examples

```

SG <- CGGPcreate(d=3, batchsize=100)
y <- apply(SG$design, 1, function(x){x[1]+x[2]^2+rnorm(1,0,.01)})
SG <- CGGPfit(SG, Y=y)
CGGPpred(SG, matrix(c(.1,.1,.1),1,3))
cbind(CGGPpred(SG, SG$design)$mean, y) # Should be near equal

```

print.CGGP	<i>Print CGGP object</i>
------------	--------------------------

Description

Default print as a list is bad since there's a lot of elements.

Usage

```

## S3 method for class 'CGGP'
print(x, ...)

```

Arguments

x	CGGP object
...	Passed to print

Value

String to be printed

Examples

```

SG = CGGPcreate(3,21)
print(SG)
f <- function(x) {x[1]+exp(x[2]) + log(x[3]+4)}
y <- apply(SG$design, 1, f)
SG <- CGGPfit(SG, y)
print(SG)

```

`rcpp_fastmatclcr` *rcpp_fastmatclcr*

Description

`rcpp_fastmatclcr`

Usage

`rcpp_fastmatclcr(I, w, MSEmat, S, maxlevel)`

Arguments

<code>I</code>	Matrix
<code>w</code>	vector
<code>MSEmat</code>	Matrix
<code>S</code>	Vector
<code>maxlevel</code>	Integer

Value

Nothing, void

`rcpp_fastmatclcranddclcr`
rcpp_fastmatclcranddclcr

Description

`rcpp_fastmatclcranddclcr`

Usage

`rcpp_fastmatclcranddclcr(I, w, MSEmat, dMSEmat, S, dS, maxlevel, numpara)`

Arguments

<code>I</code>	Matrix
<code>w</code>	vector
<code>MSEmat</code>	Matrix
<code>dMSEmat</code>	Matrix
<code>S</code>	Vector
<code>dS</code>	Matrix
<code>maxlevel</code>	Integer
<code>numpara</code>	Integer

Value

Nothing, void

<i>rcpp_gkronDBS</i>	<i>rcpp_kronDBS</i>
----------------------	---------------------

Description

rcpp_kronDBS

Usage

rcpp_gkronDBS(A, dA, B, p)

Arguments

A	Vector
dA	Vector
B	Vector
p	Vector

Value

kronDBS calculation

Examples

rcpp_gkronDBS(c(1,1), c(0,0), c(.75), c(1,1))

<i>rcpp_kronDBS</i>	<i>rcpp_kronDBS</i>
---------------------	---------------------

Description

rcpp_kronDBS

Usage

rcpp_kronDBS(A, B, p)

Arguments

A	Vector
B	Vector
p	Vector

Value

kronDBS calculation

valplot

Plot validation prediction errors

Description

Plot validation prediction errors

Usage

```
valplot(predmean, predvar, Yval, d = NULL)
```

Arguments

predmean	Predicted mean
predvar	Predicted variance
Yval	Y validation data
d	If output is multivariate, which column to use. Will do all if left as NULL.

Value

None, makes a plot

Examples

```
x <- matrix(runif(100*3), ncol=3)
f1 <- function(x){x[1]+x[2]^2}
y <- apply(x, 1, f1)
# Create a linear model on the data
mod <- lm(y ~ ., data.frame(x))
# Predict at validation data
Xval <- matrix(runif(3*100), ncol=3)
mod.pred <- predict.lm(mod, data.frame(Xval), se.fit=TRUE)
# Compare to true results
Yval <- apply(Xval, 1, f1)
valplot(mod.pred$fit, mod.pred$se.fit^2, Yval=Yval)
```

valstats	<i>Calculate stats for prediction on validation data</i>
----------	--

Description

Calculate stats for prediction on validation data

Usage

```
valstats(
  predmean,
  predvar,
  Yval,
  bydim = TRUE,
  RMSE = TRUE,
  score = TRUE,
  CRPscore = TRUE,
  coverage = TRUE,
  corr = TRUE,
  R2 = TRUE,
  MAE = FALSE,
  MIS90 = FALSE,
  metrics,
  min_var = .Machine$double.eps
)
```

Arguments

predmean	Predicted mean
predvar	Predicted variance
Yval	Y validation data
bydim	If multiple outputs, should it be done separately by dimension?
RMSE	Should root mean squared error (RMSE) be included?
score	Should score be included?
CRPscore	Should CRP score be included?
coverage	Should coverage be included?
corr	Should correlation between predicted and true mean be included?
R2	Should R ² be included?
MAE	Should mean absolute error (MAE) be included?
MIS90	Should mean interval score for 90% confidence be included? See Gneiting and Raftery (2007).
metrics	Optional additional metrics to be calculated. Should have same first three parameters as this function.
min_var	Minimum value of the predicted variance. Negative or zero variances can cause errors.

Value

data frame

References

Gneiting, Tilmann, and Adrian E. Raftery. "Strictly proper scoring rules, prediction, and estimation." *Journal of the American Statistical Association* 102.477 (2007): 359-378.

Examples

```
valstats(c(0,1,2), c(.01,.01,.01), c(0,1.1,1.9))
valstats(cbind(c(0,1,2), c(1,2,3)),
         cbind(c(.01,.01,.01),c(.1,.1,.1)),
         cbind(c(0,1.1,1.9),c(1,2,3)))
valstats(cbind(c(0,1,2), c(8,12,34)),
         cbind(c(.01,.01,.01),c(1.1,.81,1.1)),
         cbind(c(0,1.1,1.9),c(10,20,30)), bydim=FALSE)
valstats(cbind(c(.8,1.2,3.4), c(8,12,34)),
         cbind(c(.01,.01,.01),c(1.1,.81,1.1)),
         cbind(c(1,2,3),c(10,20,30)), bydim=FALSE)
```

Index

* CGGP core functions

CGGPappend, 3
CGGPcreate, 4
CGGPfit, 5
predict.CGGP, 32

* CGGP plot functions

CGGPplotblocks, 6
CGGPplotcorr, 7
CGGPplotheat, 8
CGGPplothist, 9
CGGPplotsamplesneglogpost, 10
CGGPplotslice, 11
CGGPplottheta, 12
CGGPplotvariogram, 13
CGGPvalplot, 13

* correlation functions

CGGP_internal_CorrMatCauchy, 18
CGGP_internal_CorrMatCauchySQ, 19
CGGP_internal_CorrMatCauchySQT, 20
CGGP_internal_CorrMatGaussian, 21
CGGP_internal_CorrMatMatern32, 22
CGGP_internal_CorrMatMatern52, 23
CGGP_internal_CorrMatPowerExp, 24
CGGP_internal_CorrMatWendland0, 25
CGGP_internal_CorrMatWendland1, 26
CGGP_internal_CorrMatWendland2, 27

CGGP, 3

CGGP-package (CGGP), 3

CGGP_internal_calcMSE, 15

CGGP_internal_calcMSEde, 16

CGGP_internal_calcpw, 16

CGGP_internal_calcpwanddpw, 17

CGGP_internal_CorrMatCauchy, 18, 19, 20,
22–28

CGGP_internal_CorrMatCauchySQ, 18, 19,
20, 22–28

CGGP_internal_CorrMatCauchySQT, 18, 19,
20, 22–28

CGGP_internal_CorrMatGaussian, 18–20,
21, 23–28

CGGP_internal_CorrMatMatern32, 18–20,
22, 22, 24–28

CGGP_internal_CorrMatMatern52, 18–20,
22, 23, 23, 25–28

CGGP_internal_CorrMatPowerExp, 18–20,
22–24, 24, 26–28

CGGP_internal_CorrMatWendland0, 18–20,
22–25, 25, 27, 28

CGGP_internal_CorrMatWendland1, 18–20,
22–26, 26, 28

CGGP_internal_CorrMatWendland2, 18–20,
22–27, 27

CGGP_internal_gneglogpost, 28

CGGP_internal_MSEpredcalc, 29

CGGP_internal_neglogpost, 30

CGGP_internal_set_corr, 31

CGGPappend, 3, 5, 6, 32

CGGPcreate, 3, 4, 6, 32

CGGPfit, 3, 5, 5, 32

CGGPplotblocks, 6, 8–14

CGGPplotblockselection, 7

CGGPplotcorr, 6, 7, 9–14

CGGPplotheat, 6, 8, 8, 10–14

CGGPplothist, 6, 8, 9, 9, 11–14

CGGPplotsamplesneglogpost, 6, 8–10, 10,
12–14

CGGPplotslice, 6, 8–11, 11, 12–14

CGGPplottheta, 6, 8–12, 12, 13, 14

CGGPplotvariogram, 6, 8–12, 13, 14

CGGPpred (predict.CGGP), 32

CGGPvalplot, 6, 8–13, 13

CGGPvalstats, 14

plot.CGGP, 31

predict.CGGP, 3, 5, 6, 32

print.CGGP, 33

rcpp_fastmatclr, 34

`rcpp_fastmatclcranddclcr`, [34](#)

`rcpp_gkronDBS`, [35](#)

`rcpp_kronDBS`, [35](#)

`valplot`, [36](#)

`valstats`, [37](#)