

Package ‘GARChSK’

July 21, 2025

Type Package

Title Estimating a GARChSK Model and GJRsk Model

Version 0.1.0

Description Functions for estimating a GARChSK model and GJRsk model based on a publication by Leon et,al (2005)<[doi:10.1016/j.qref.2004.12.020](https://doi.org/10.1016/j.qref.2004.12.020)> and Nakagawa and Uchiyama (2020)<[doi:10.3390/math8111990](https://doi.org/10.3390/math8111990)>. These are a GARCH-type model allowing for time-varying volatility, skewness and kurtosis.

License GPL (>= 2)

LazyData TRUE

Imports stats, Rsolnp

RoxygenNote 6.0.1

NeedsCompilation no

Author Kei Nakagawa [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5046-8128>>)

Maintainer Kei Nakagawa <kei.nak.0315@gmail.com>

Repository CRAN

Date/Publication 2021-07-22 07:00:07 UTC

Contents

GARChSK	2
garchsk_construct	2
garchsk_est	3
garchsk_fcst	3
garchsk_ineqfun	4
garchsk_lik	4
GBP	5
gjrsk_construct	5
gjrsk_est	6
gjrsk_fcst	6
gjrsk_ineqfun	7
gjrsk_lik	7

kurtosis	8
skewness	8

Index	9
--------------	----------

GARCHSK	<i>GARCHSK</i>
---------	----------------

Description

Functions for estimating GARCHSK model and GJRSK model based on a publication by Leon et,al (2005).

garchsk_construct	<i>This function constructs GARCHSK model of given data and parameters.</i>
-------------------	-----------------------------------------------------------------------------

Description

This function constructs GARCHSK model of given data and parameters.

Usage

```
garchsk_construct(params, data)
```

Arguments

params	vector of GJRSK model parameters(p1,const2,p2,q2,const3,p3,q3,const4,p4,q4)
data	vector time series data

Value

list of conditional mean(mu), variance(h), skewness(sk) and kurtosis(ku)

`garchsk_est`*This function estimates GARCHSK model's parameters.*

Description

This function estimates GARCHSK model's parameters.

Usage

```
garchsk_est(data)
```

Arguments

`data` vector time series data

Value

list of parameters, standard errors of parameters, t-statistics, the minimum value of log-likelihood, AIC and BIC.

Examples

```
library(GARCHSK)
#load data
data(GBP)

# Estimate the parameters of GARCHSK model
garchsk_GBP<-garchsk_est(GBP[1:100])

# Parameters
garchsk_GBP$params
```

`garchsk_fcst`*This function forecasts conditional mean, variance, skewness and kurtosis with given GARCHSK model.*

Description

This function forecasts conditional mean, variance, skewness and kurtosis with given GARCHSK model.

Usage

```
garchsk_fcst(params, data, max_forecast = 20)
```

Arguments

params	vector of GARCHSK model parameters(p1,const2,p2,q2,const3,p3,q3,const4,p4,q4)
data	vector time series data
max_forecast	how long does this function forecast(Default value is 20)

Value

list of predicted conditional mean,variance,skewness and kurtosis

garchsk_ineqfun	<i>This function is inequality equation of GARCHSK parameters used in optimization process(Rsolnp).</i>
-----------------	---------------------------------------------------------------------------------------------------------

Description

This function is inequality equation of GARCHSK parameters used in optimization process(Rsolnp).

Usage

```
garchsk_ineqfun(params, data)
```

Arguments

params	vector of GARCHSK model parameters(p1,const2,p2,q2,r2,const3,p3,q3,r3,const4,p4,q4,r4)
data	vector time series data

Value

upper bound >parameters > lower bound

garchsk_lik	<i>This function calculates the log-likelihood of GARCHSK model.</i>
-------------	----------------------------------------------------------------------

Description

This function calculates the log-likelihood of GARCHSK model.

Usage

```
garchsk_lik(params, data)
```

Arguments

params	vector of GARCHSK model parameters(p1,const2,p2,q2,const3,p3,q3,const4,p4,q4)
data	vector time series data

Value

(negative) log-likelihood of GJRSK model

GBP	<i>GBP/USD exchange rate from 1990-01-03 to 2002-5-3 from Bloomberg.</i>
-----	--------------------------------------------------------------------------

Description

GBP/USD exchange rate from 1990-01-03 to 2002-5-3 from Bloomberg.

Format

A numeric vector with 3218 length

Source

Bloomberg(GBP CURRENCY)

<code>gjrsk_construct</code>	<i>This function constructs GJRSK model of given data and parameters.</i>
------------------------------	---------------------------------------------------------------------------

Description

This function constructs GJRSK model of given data and parameters.

Usage

```
gjrsk_construct(params, data)
```

Arguments

params	vector of GJRSK model parameters(p1,const2,p2,q2,r2,const3,p3,q3,r3,const4,p4,q4,r4)
data	vector time series data

Value

list of conditional mean(mu), variance(h), skewness(sk) and kurtosis(ku)

`gjrsk_est`*This function estimates GJRSK model's parameters.*

Description

This function estimates GJRSK model's parameters.

Usage

```
gjrsk_est(data)
```

Arguments

`data` vector time series data

Value

list of parameters, standard errors of parameters, t-statistics, the minimum value of log-likelihood, AIC and BIC.

Examples

```
library(GARCHSK)
#load data
data(GBP)

# Estimate the parameters of GJR-SK model
gjrsk_GBP<-gjrsk_est(GBP[1:100])

# Parameters
gjrsk_GBP$params
```

`gjrsk_fcst`*This function forecasts conditional mean, variance, skewness and kurtosis with given GJRSK model.*

Description

This function forecasts conditional mean, variance, skewness and kurtosis with given GJRSK model.

Usage

```
gjrsk_fcst(params, data, max_forecast = 20)
```

Arguments

params	vector of GJRSK model parameters(p1,const2,p2,q2,r2,const3,p3,q3,r3,const4,p4,q4,r4)
data	vector time series data
max_forecast	how long does this function forecast(Default value is 20)

Value

list of predicted conditional mean,variance,skewness and kurtosis

gjrsk_ineqfun	<i>This function is inequality equation of GJRSK parameters used in optimization process(Rsolnp).</i>
---------------	-------------------------------------------------------------------------------------------------------

Description

This function is inequality equation of GJRSK parameters used in optimization process(Rsolnp).

Usage

```
gjrsk_ineqfun(params, data)
```

Arguments

params	vector of GJRSK model parameters(p1,const2,p2,q2,r2,const3,p3,q3,r3,const4,p4,q4,r4)
data	vector time series data

Value

upper bound >parameters > lower bound

gjrsk_lik	<i>This function calculates the log-likelihood of GJRSK model.</i>
-----------	--------------------------------------------------------------------

Description

This function calculates the log-likelihood of GJRSK model.

Usage

```
gjrsk_lik(params, data)
```

Arguments

params	vector of GJRSK model parameters(p1,const2,p2,q2,r2,const3,p3,q3,r3,const4,p4,q4,r4)
data	vector time series data

Value

(negative) log-likelihood of GJRSK model

kurtosis	<i>This function calculates kurtosis of given data.</i>
----------	---------------------------------------------------------

Description

This function calculates kurtosis of given data.

Usage

```
kurtosis(data)
```

Arguments

data vector or T by 1 matrix

Value

kurtosis of given data

skewness	<i>This function calculates skewness of given data.</i>
----------	---------------------------------------------------------

Description

This function calculates skewness of given data.

Usage

```
skewness(data)
```

Arguments

data vector or T by 1 matrix

Value

skewness of given data

Index

GARCHSK, [2](#)
GARCHSK-package (GARCHSK), [2](#)
garchsk_construct, [2](#)
garchsk_est, [3](#)
garchsk_fcst, [3](#)
garchsk_ineqfun, [4](#)
garchsk_lik, [4](#)
GBP, [5](#)
gjrsk_construct, [5](#)
gjrsk_est, [6](#)
gjrsk_fcst, [6](#)
gjrsk_ineqfun, [7](#)
gjrsk_lik, [7](#)

kurtosis, [8](#)

skewness, [8](#)