

Package ‘PACVr’

July 21, 2025

Version 1.0.11

Date 2024-04-08

Title Plastome Assembly Coverage Visualization

Maintainer Michael Gruenstaeudl <m_gruenstaeudl@fhsu.edu>

Depends R (>= 3.3.0)

Imports Biostrings (>= 2.48.0), dplyr, GenomicAlignments (>= 1.18.1),
GenomicRanges, IRanges, logger, read.gb (>= 2.2), RCircos (>= 1.2.0), grDevices, stats, utils, tidyR, R6

Description Visualizes the coverage depth of a complete plastid genome as well as the equality of its inverted repeat regions in relation to the circular, quadripartite genome structure and the location of individual genes. For more information, please see Gruenstaeudl and Jenke (2020) <[doi:10.1186/s12859-020-3475-0](https://doi.org/10.1186/s12859-020-3475-0)>.

License BSD 3-clause License + file LICENSE

RoxygenNote 7.3.1

URL <https://github.com/michaelgruenstaeudl/PACVr>

BugReports <https://github.com/michaelgruenstaeudl/PACVr/issues>

Suggests testthat (>= 3.0.0), rentrez

Config/testthat/edition 3

Encoding UTF-8

NeedsCompilation no

Author Gregory Smith [ctb],
Nils Jenke [ctb],
Michael Gruenstaeudl [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-1666-1773>>)

Repository CRAN

Date/Publication 2024-04-10 03:00:03 UTC

Contents

PACVr.complete	2
RCircos.Env	3

PACVr.complete *Execute the complete pipeline of PACVr*

Description

This function executes the complete pipeline of **PACVr** via a single command.

Usage

```
PACVr.complete(
  gbkFile,
  bamFile,
  windowSize = 250,
  logScale = FALSE,
  threshold = 0.5,
  IRCheck = NA,
  relative = TRUE,
  textSize = 0.5,
  tabularCovStats = FALSE,
  output = NA
)
```

Arguments

gbkFile	a character string that specifies the name of, and path to, the GenBank input file; alternatively, a character string of GenBank data
bamFile	a character string that specifies the name of, and path to, the BAM input file
windowSize	a numeric value that specifies window size in which the coverage is calculated
logScale	a boolean that specifies if the coverage depth is to be log-transformed before visualizing it
threshold	a numeric value that specifies the threshold for plotting coverage depth bars in red as opposed to the default black
IRCheck	a numeric value that specifies if tests for IRs of input genome should be performed, and - if IRs are present - which line type to be used for visualizing gene synteny between IRs; 0 = IR presence test but no synteny visualization, 1 = IR presence test and synteny visualization, with ribbon lines between IRs, 2 = IR presence test and synteny visualization, with solid lines between IRs, otherwise = neither IR presence test nor synteny visualization
relative	a boolean that specifies whether the threshold is a relative value of the average coverage instead of an absolute value
textSize	a numeric value that specifies the relative font size of the text element in the visualization
tabularCovStats	a boolean, that when TRUE, generates additional files with detailed genomic region information
output	a character string that specifies the name of, and path to, the output file

Value

A file in pdf format containing a circular visualization of the input plastid genome and its sequence reads. As a function, returns 0 in case of visualization success.

Examples

```
## Not run:
gbkFile <- system.file("extdata", "NC_045072/NC_045072.gb", package="PACVr")
bamFile <- system.file("extdata", "NC_045072/NC_045072_subsampld.bam", package="PACVr")
outFile <- paste(tempdir(), "/NC_045072__all_reads.pdf", sep="")
PACVr.complete(gbkFile=gbkFile, bamFile=bamFile, windowSize=250, logScale=FALSE,
               threshold=0.5, IRCheck=1, relative=TRUE, textSize=0.5,
               tabularCovStats=FALSE, output=outFile)

## End(Not run)
## Not run:
gbkFile <- system.file("extdata", "MG936619/MG936619.gb", package="PACVr")
bamFile <- system.file("extdata", "MG936619/MG936619_subsampld.bam", package="PACVr")
outFile <- paste(tempdir(), "/MG936619_CoverageViz.pdf", sep="")
PACVr.complete(gbkFile=gbkFile, bamFile=bamFile, windowSize=50, logScale=FALSE,
               threshold=0.5, IRCheck=NA, relative=TRUE, textSize=0.5,
               tabularCovStats=FALSE, output=outFile)

## End(Not run)
```

 RCircos.Env

Export the custom environment 'RCircos.Env'

Description

This function exports the custom environment 'RCircos.Env' used by **RCircos**.

Details

PACVr employs **RCircos** as its visualization engine. In its operation, **RCircos** defines a custom environment (called 'RCircos.Env') and reads/writes variables to this environment from various of its functions. In order to make this environment accessible to **RCircos** within **PACVr** and, simultaneously, fulfil the requirements of CRAN, this export command was created. For more information, please see the Stackoverflow post at <https://stackoverflow.com/questions/56875962/r-package-transferring-environment-from-imported-package>.

Index

PACVr.complete, [2](#)

RCircos.Env, [3](#)